



Section A-A

REVISION RECORD				
REV	ECO	DESCRIPTION	DRFT	DATE
△		图面更新	CSX	04/18/06
△		工程变更	CSX	11/30/06
△		增加UL刻字	CSX	03/12/07
△		品名、料号增加环保标示"00"	LJH	12/11/07
△		增加VDE、CE刻字	WLM	02/10/09

Notes:

1. Pitch:5.0mm , Poles:2-24P
2. Rated voltage/current:UL 300V/15A  
VDE 320V/10A
3. Operation temperatures:-45°C~+105°C
4. Withstanding Voltage:AC2000V/1min
5. Insulation Resistance:5000 Ω/DC1000V
6. Wire Range:28~12AWG, 2.5mm<sup>2</sup>
7. Max. Torque Value:M2.5, 4.08kgf.cm
8. Undimensioned Tolerances:

Pitch range in mm		Nominal dimension range in mm					
to	over	to	over	to	over	over	
6	6 to 10	10 to 24	30 to 60	60 to 100	100 to 150	150	∩
	±0.10	±0.15	±0.25	±0.2	±0.3	±0.5	±0.7
							±1.0
							0.05/0.10

5	2EDGKA/B-5.0 COVER	1030COYXXA (H)	1	PA66	UL94V-0
4	2EDGKA/B-CLAMP	1028B00010 (H)	XX	Phospor Bronze	Ni plated
3	2EDG SCREW-M2.5	S000000980 (H)	△	Steel	Cr <sup>3+</sup> Zn
2	DG128 CAGE	X000000020 (H)	XX	Brass	Ni plated



ITEM	NAME OF PART	NO. OF PART	Q*TY	MATERIAL	NOTES
1	2EDGKA/B-5.0 HOUSING	1030A0YXXA (H)	1	PA66	UL94V-0

  

TOLERANCES EXCEPT AS NOTED MM (INCH) .0 ± .00 ± .000 ± ANGLES ± 1° THIRD ANGLE PROJECTION	DFTO WYP CHKD MFO APPVL G.E. FINISH: SCALE:	DATE 04/22/04 DATE DATE DATE 2/17/09 MATERIAL: DATE	宁波高正电子有限公司 DEGSON ELECTRONICS CO., LTD NAME 2EDGKB-5.0-XXP-1Y-00A(H) DRAWING NO. 2EDGKB-5.0-E01 /PART NO. DO NOT SCALE DRAWING	SIZE A3 REV T5 02/10/09	SHEET 1 OF 1
---	---	--	--	-------------------------------------	--------------