

Technical Data // STLZ1570/..G-3.81-H-GREEN

Spacing 3.81 mm

**Highlights**

2 to 20 poles

Horizontal pin strip

Spacing 3.81 mm

Closed ends

Double tier pin strip

Wire Sizes

Solid min	-
Solid max	-
Stranded (flexible) min	-
Stranded (flexible) max	-
Stranded with ferrule min	-
Stranded with ferrule max	-

Dimensions

PCB hole diameter	1.2 mm
-------------------	--------

Materials

Contact pin	Copper Alloy
-------------	--------------

Insulating Material

Material	PBT
Flammability class	UL 94 V-0

Temperatures

Operating temperature (without mech. load)	-40 °C - 105 °C
Store temperature	-40 °C - 105 °C

Wave Soldering Process

Soldering temperature, recommended	260 °C
Peak soldering time, recommended	3-4 s

Reflow Process

Soldering temperature, recommended	-
Peak soldering time, recommended	-

Technical Data // STLZ1570/..G-3.81-H-GREEN

Spacing 3.81 mm

Colours

GREEN, RAL 6018

LIGHT GREEN, similar RAL 6018

Colours according to RAL, there may be variations on colour due to production conditions.
Special colours on request.

Ratings

				
UseGroup	B	C	D	
Rated voltage	300 V	-	300 V	160 V
Rated current	10 A	-	10 A	10 A
Overvoltage category				III
Test voltage	1.60 kV	-	1.60 kV	2.5 kV
Pollution degree				3



Counterparts (Spacing 3.81 mm)

Terminal Block

AKZ1550	AKZ1700	AKZ1710	AKZ4551	AKZ4561
---------	---------	---------	---------	---------

In combination of connectors with different admission data, the lower value is valid.

Accessoires

Figure	Designation	Article Number
	Coding Star CS1-3.5/3.81-RED	Order Data: 50000000023
	Separating Element SE-STL1550-GREEN	Order Data: 51550000002

Technical Data // STLZ1570/..G-3.81-H-GREEN

Spacing 3.81 mm

Order Data (Spacing 3.81 mm)

Number of Poles	Width (mm)	Article Designation	Article Number	PU
2	9.01	STLZ1570/2G-3.81-H-GREEN	51570025021 E	100
3	12.82	STLZ1570/3G-3.81-H-GREEN	51570035021 E	100
4	16.63	STLZ1570/4G-3.81-H-GREEN	51570045021 E	100
5	20.44	STLZ1570/5G-3.81-H-GREEN	51570055021 E	100
6	24.25	STLZ1570/6G-3.81-H-GREEN	51570065021 E	100
7	28.06	STLZ1570/7G-3.81-H-GREEN	51570075021 D	50
8	31.87	STLZ1570/8G-3.81-H-GREEN	51570085021 D	50
9	35.68	STLZ1570/9G-3.81-H-GREEN	51570095021 D	50
10	39.49	STLZ1570/10G-3.81-H-GREEN	51570105021 D	50
11	43.30	STLZ1570/11G-3.81-H-GREEN	51570115021 D	50
12	47.11	STLZ1570/12G-3.81-H-GREEN	51570125021 D	50
13	50.92	STLZ1570/13G-3.81-H-GREEN	51570135021 D	50
14	54.73	STLZ1570/14G-3.81-H-GREEN	51570145021 D	50
15	58.54	STLZ1570/15G-3.81-H-GREEN	51570155021 D	50
16	62.35	STLZ1570/16G-3.81-H-GREEN	51570165021 D	50
17	66.16	STLZ1570/17G-3.81-H-GREEN	51570175021 D	50
18	69.97	STLZ1570/18G-3.81-H-GREEN	51570185021 D	50
19	73.78	STLZ1570/19G-3.81-H-GREEN	51570195021 D	50
20	77.59	STLZ1570/20G-3.81-H-GREEN	51570205021 D	50

Technical drawing

