



REVISION RECORD				
REV	ECN	DESCRIPTION	DRFT	DATE
△		Drawing emend	csx	04/04/06
△		更新图面	LJH	04/16/08
△	10-0329	增加标注尺寸	COCO	10/07/10
△	11-0035	改善螺帽掉落, 改用变更后零件与螺帽	HD	03/08/11
△	11-0255	修改螺帽孔结构	ZMT	10/17/11
△	14-0107	黄铜变紫铜, 料号变更; 工频耐压变更为额定冲击电压	WL	10/29/14

- NOTES:
- 1.DIMENSION SHALL BE INTERPRETED PER ASME Y14.5-2009.
  - 2.PITCH: 5.08MM ,POLES: 2-22P
  - 3.RATED VOLTAGE/CURRENT: UL 300V/15A VDE 320V/20A
  - 4.OPERATION TEMPERATURES: -40℃~+105℃
  - 5.RATED IMPULSE VOLTAGE: 4.0KV
  - 6.INSULATION RESISTANCE: 5000MΩ/DC1000V
  - 7.UNDIMENSIONED TOLERANCES:

	Pitch range in mm		Nominal dimension range in mm				—		
	over 6 to 10	over 10 to 24	over 30 to 60	over 60 to 100	over 100 to 150	over 150			
to 6	±0.10	±0.15	±0.25	±0.2	±0.3	±0.5	±0.7	±1.0	0.05/0

ITEM	NAME OF PART	NO. OF PART	QTY	MATERIAL	NOTES
3	2EDGR(A)-PIN HEADER(1*8.25*8.7)	1008B00330(H)	XX	COPPER	SN PLATED
2	2EDGK SCREW CAP	S000001040(H)	2	BRASS	
1	2EDGRM-5.08-HOUSING	1012A0YXXC(H)	1	PA66	UL94V-0

MM (INCH) TOLERANCES EXCEPT AS NOTED .X ±     .X' ± .XX ±    .XX' ± .XXX ±   .XXX' ±		MATERIAL: FINISH: PART NO.:		宁波高正电子有限公司 <b>DEGSON</b> ® DEGSON ELECTRONICS CO., LTD	
ANGLES ± 1° THIRD ANGLE PROJECTION		APPD: CHKD: <i>Aaron 10/31/14</i> DRFT: WL 10/29/14		NAME: 2EDGRM-5.08-XXP-1Y-00A(H)	
TITLE: ASSEMBLY DRAWING DRAWING NO.: 2EDGRM-5.08-E03 DO NOT SCALE DRAWING				SCALE: N/A	REV: T6 SHEET: 1/1