



PCB LAYOUT

REVISION RECORD				
REV	ECN	DESCRIPTION	DRFT	DATE

NOTES1:

- UL Standard
- 1.Rated Voltage/Current : 300V / 8A
- 2.Withstanding Voltage : AC1600V/1Min.
- VDE Standard

1. Pollution Degree	2
Overvoltage Category	II
Rate Impulse Voltage(KV)	2.5KV
Rate Voltage(V)	250V
Rate Current(A)	7A

NOTES2:

- 1.Dimension shall be interpreted per ASME Y14.5-2009
- 2.Pitch : 3.50mm, Poles : N=2~24P
- 3.Operating temperature: -40°C~+105°C
- 4.Undimensioned Tolerances:

Pitch Range In mm		Nominal Dimension Range In mm				-	∩	D
TO	Over	Over	TO	Over	Over	Over	Over	0.1/10
6	10	24	30	60	100	150		<
±0.15	±0.20	±0.30	±0.30	±0.50	±0.70	±1.00	±1.30	±2

5.RoHS Compliance



2	PIN	COPPER ALLOY	Sn Plated
1	HOUSING	PA66	UL94V-0
ITEM	NAME OF PART	MATERIAL	NOTES

DETACHED LISTS	PART NO.:		NINGBO DEGSON ELECTRICAL CO., LTD	
	NAME:		15EDGVC-3.5-XXP-1Y-00A(H)	
	TITLE:		CUSTOMER DRAWING	REV TO
	DRAWING NO.:		15EDGVC-3.5-C02	SHEET 1/1
	SCALE:		DO NOT SCALE DRAWING	SCALE 1:1



THIRD ANGLE PROJECTION