










未标尺寸请参考3D文件



02P



03P



Pitch Range In mm		Nominal		Dimension Range In mm					
TO	Over	Over	TO	Over	Over	Over	Over	TO	
6	6	10	30	30	60	100	150	150	0.1/10
±0.15	±0.20	±0.30	±0.30	±0.50	±0.70	±1.00	±1.30	±2'	

5	Spring	Stainless steel	
4	Clamp	Copper alloy	Sn plated
3	Cover	PA66	UL94V-0
2	housing 2	PA66	UL94V-0
1	housing 1	PA66	UL94V-0
ITEM	NAME OF PART	MATERIAL	NOTES
UL 标准/UL Standard:			
额定电压/电流/Rated Voltage(V)/Current(A)		B	C D
IEC 标准/IEC Standard:		300/15	150/15 300/10
过压类别/Overvoltage Category/污染等级/Pollution Degree		III/3	III/2 II/2
额定电压/电流/Rated Voltage(V)/Current(A)		320/20	/ /
额定脉冲电压(kV)/Rate Impulse Voltage(kV)		4	/ /
线径范围(硬线和软线)/Wire Range(rigid and flexible)(mm <sup>2</sup> /AWG)		0.2~2.5/22~14	
间距/Pitch(mm)/线数范围/Poles		5.0/N=02~24P	
剥线长度/Stripping length(mm)		9-10	
使用温度范围/Operating temperature(°C)		-40~+105	
符合RoHS环保要求/Conform to RoHS		Yes	
标准颜色编号/Standard color number:		PANTONE 428C	

MATERIAL: /	SURFACE: /		
MAT NO.: /	<b>宁波高松电子有限公司</b> <b>NINGBO DEGSON ELECTRICAL CO., LTD</b>		
STATUS: /			
APPD:	NAME:		
CHKD:	<b>8EDGKF-5.0-XXP-11-01A(H)</b>		
DRFT: YHG 2011.04.27	DRAWING NO.: 8EDGKF-5.0-C03		REV TO
⊕	SIZE: A4	TYPE: CUSTOMER DRAWING	SCALE: 1:1 SHEET 1/1

REV	ECN	DESCRIPTION	DRFT	DATE