



REVISION RECORD				
REV	ECO	DESCRIPTION	DRFT	DATE
△		图面更新	CSX	04/18/06
△		工程变更	CSX	11/30/06
△		增加UL刻字	CSX	03/12/07
△		品名、料号增加环保标示“00”	LJH	12/11/07
△		增加VDE、CE刻字	WLM	02/10/09

Notes:

- Pitch: 5.0mm, Poles: 2-24P
- Rated voltage/current: UL 300V/15A
VDE 320V/10A
- Operation temperatures: -45°C ~ +105°C
- Withstanding Voltage: AC2000V/1min
- Insulation Resistance: 5000 Ω / DC1000V
- Wire Range: 28~12AWG, 2.5mm²
- Max. Torque Value: M2.5, 4.08kgf.cm
- Undimensioned Tolerances:

Pitch range in mm		Nominal dimension range in mm						
to	over	to	over	to	over	over		
6	6	10	10	30	60	100	150	∩
6	10	24	30	60	100	150		□
±0.10	±0.15	±0.25	±0.2	±0.3	±0.5	±0.7	±1.0	0.05/10

5	2EDGKA/B-5.0 COVER	1030COYXXA (H)	1	PA66	UL94V-0
4	2EDGKA/B-CLAMP	1028B00010 (H)	XX	Phospor Bronze	Ni plated
3	2EDG SCREW-M2.5	S000000980 (H)	△	Steel	Cr ³⁺ Zn
2	DG128 CAGE	X000000020 (H)	XX	Brass	Ni plated

Section A-A



ITEM	NAME OF PART	NO. OF PART	Q'TY	MATERIAL	NOTES
1	2EDGKA/B-5.0 HOUSING	1030A0YXXA (H)	1	PA66	UL94V-0

MM (INCH)	DFTO WYP	DATE 04/22/04
CHKD	DATE	
TOLERANCES EXCEPT AS NOTED		
MFO	DATE	
APPVL	DATE 2/17/09	
MATERIAL :		
ANGLES ± 1'	G.E. :	
THIRD ANGLE PROJECTION	FINISH :	
SCALE :	DO NOT SCALE DRAWING	

宁波高正电子有限公司 DEGSON ELECTRONICS CO., LTD	
NAME 2EDGKB-5.0-XXP-1Y-00A(H)	
DRAWING NO. 2EDGKB-5.0-E01	SIZE A3
/PART NO.	REV T5 02/10/09
SHEET 1 OF 1	