




Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless explicit authorization is granted. Violations will be liable for compensation. All rights reserved for patent, utility, model or designs registrations. 除非给予明确授权，否则禁止转让、复制、利用、交还本文件的内容。侵犯者将负赔偿责任。实用新型和外专利的所有权利。



尺寸公差(mm)					0.05/10 ±T
0 ~ 30	>30 ~ 60	>60 ~ 100	>100 ~ 150	>150	
±0.20	±0.30	±0.50	±0.70	±1.00	

Rated current	16A
Rated voltage	300V
Coil/Contact dielectric voltage	2000V/S
Dielectric voltage between contact	2000V/S
Screw torque	1.0Nm
External connection wire	20-14/0.5-2.5W G/mm <sup>2</sup>
Ambient temperature	-45~+65 °C
Key controlled symbol	*

Conform to RoHS

Printing for laser marking, printing content is clear ,no broken line,ect

Seal literal reference according to the foot position in the drawing

1	DSRT05A-E3-00A(H)-N	30019000130	1		
NO.	DESCRIPTION	MATERIAL NO.	QTY	MATERIAL	NOTES
MATERIAL: /		SURFACE: /			
MAT.NO.: 30020000059		宁波高松电子有限公司 NINGBO DEGSON ELECTRICAL CO., LTD			
STATUS: /					
APPD:		Description: DSRT05A-E3-00A(H)			
CHKD:		DRAWING NO.: 30000367			
DRFT: /		REV		TO-1	
SIZE: A4		TYPE: PRODUCT DRAWING		SCALE: 1:1 SHEET 1/1	



REV	ECN	DESCRIPTION	DRFT	DATE