



Highlights

- 2 to 12 poles
- 2 and 3 pole modules
- Spacing 7.5 mm
- Wire guard type
- Wire entry parallel to PCB
- Test jack on every clamping point
- 32 A max. with 4.0 mm² wire

Wire Sizes

Solid min	0.2 mm ²
Solid max	4.0 mm ²
Stranded (flexible) min	0.2 mm ²
Stranded (flexible) max	2.5 mm ²
Stranded with ferrule min	0.2 mm ²
Stranded with ferrule max	2.5 mm ²

Dimensions

Stripped length	7.0 mm
PCB hole diameter	2.0 mm

Materials

Clamp	Brass
Wire guard	Stainless Steel
Screw	Steel

Insulating Material

Material	PA 6.6
Flammability class	UL 94 V-0

Temperatures

Operating temperature	-40 °C (without mech. load) - 105 °C
Store temperature	-40 °C - 105 °C

**Technical Data // AK114/..DS-7.5-V-GREY**

Spacing 7.5 mm

Wave Soldering Process

Soldering temperature, recommended 260 °C

Peak soldering time, recommended 3-4 s

Reflow Process

Soldering temperature, recommended -

Peak soldering time, recommended -

Colours

GREY, RAL 7016

Colours according to RAL, there may be variations on colour due to production conditions.
Special colours on request.**Ratings**

UseGroup	UL US			VDE	
	B	C	D		
Rated voltage	300 V	150 V	300 V		750 V
Rated current	20 A	10 A	20 A		32 A
Rated wire size				min	max
- solid	AWG 22-12	AWG 22-12	AWG 22-12	0.5 mm ²	4.0 mm ²
- stranded	-	-	-	-	-
- stranded (flexible)	AWG 22-12	AWG 22-12	AWG 22-12	0.5 mm ²	4.0 mm ²
Torque	0.80 Nm	0.80 Nm	0.80 Nm		0.50 Nm
Screw size	M3	M3	M3		M3
Test voltage	1.60 kV	1.30 kV	1.60 kV		3.0 kV

Accessoires

Figure	Designation	Article Number
	Bridge, 2-pole, insulated, BRI/2-7.5/7.62-L8.2-LIGHT GREY	Art.-Nr. 50000000017



Technical Data // **AK114/..DS-7.5-V-GREY**

Spacing 7.5 mm

Order Data (Spacing 7.5 mm)

Number of Poles	Width (mm)	Article Designation	Article Number	PU
2	15.70	AK114/2DS-7.5-V-GREY	50114020070 F	200
3	23.20	AK114/3DS-7.5-V-GREY	50114030070 F	200
4	30.70	AK114/4DS-7.5-V-GREY	50114040070 F	200
5	38.20	AK114/5DS-7.5-V-GREY	50114050070 E	100
6	45.70	AK114/6DS-7.5-V-GREY	50114060070 E	100
7	53.20	AK114/7DS-7.5-V-GREY	50114070070 E	100
8	60.70	AK114/8DS-7.5-V-GREY	50114080070 E	100
9	68.20	AK114/9DS-7.5-V-GREY	50114090070 E	100
10	75.70	AK114/10DS-7.5-V-GREY	50114100070 D	50
11	83.20	AK114/11DS-7.5-V-GREY	50114110070 D	50
12	90.70	AK114/12DS-7.5-V-GREY	50114120070 D	50

Technical drawing

