

Specifications:
 Current rating: 3.0A AC, DC
 Voltage rating: 250V AC, DC
 Contact resistance: 20m ohm max.
 Insulation resistance: 1000M ohm min.
 Withstanding voltage: 500V AC/minute
 Operating Temperature range: -40°C to +105°C


Material:
 Insulator: PBT (UL94V-0)
 Standard Color:Black
 Contact: Brass
 Finish: Gold/Tin/Selective Gold Plated

How To Order:
 2212S-XXX-85

Plastic Height 8.5mm
 G:Gold Plated
 T:Tin Plated
 SG:Selective Gold Plated
 No. Of Contact
 S:Straight

Dimension :

Poles	DIM:(mm)		Poles	DIM:(mm)		Poles	DIM:(mm)		Poles	DIM:(mm)	
	A	B		A	B		A	B		A	B
2	5.58	2.54	12	30.98	27.94	22	56.38	53.34	32	81.78	78.74
3	8.12	5.08	13	33.52	30.48	23	58.92	55.88	33	84.32	81.28
4	10.66	7.62	14	36.06	33.02	24	61.46	58.42	34	86.86	83.82
5	13.20	10.16	15	38.60	35.56	25	64.00	60.96	35	89.40	86.36
6	15.74	12.70	16	41.14	38.10	26	66.54	63.50	36	91.94	88.90
7	18.28	15.24	17	43.68	40.64	27	69.08	66.04	37	94.48	91.44
8	20.82	17.78	18	46.22	43.18	28	71.62	68.58	38	97.02	93.98
9	23.36	20.32	19	48.76	45.72	29	74.16	71.12	39	99.56	96.52
10	25.90	22.86	20	51.30	48.26	30	76.70	73.66	40	102.1	99.06
11	28.44	25.40	21	53.84	50.80	31	79.24	76.20			



P.C.B. layout

RoHS Compliant

E				DRAWN: Romina Wu	GENERAL TOLERANCE: .X=±0.2 .XX=±0.15	Neltron Industrial Co., Ltd.	DESCRIPTION: 2.54mm PCB Socket Single Row Straight	SIZE A4
D				CHECKED: Jerry Chen	UNIT: MM			
C				APPROVAL: Mike Wu	SCALE:	PART NO: 2212S-XXX-85		
B					SHEET: 1 / 1			PROJECTION:
A	06-Dec-2018		Romina Wu					
REV	DATE	FILE	BY					