



### Highlights

2 to 12 poles

2 and 3 pole modules

Spacing 5.0 mm

Lift type

Wire entry vertical to PCB

24 A with 2.5 mm<sup>2</sup> wire

### Wire Sizes

Solid min 0.2 mm<sup>2</sup>

Solid max 4.0 mm<sup>2</sup>

Stranded (flexible) min 0.2 mm<sup>2</sup>

Stranded (flexible) max 2.5 mm<sup>2</sup>

Stranded with ferrule min 0.25 mm<sup>2</sup>

Stranded with ferrule max 2.5 mm<sup>2</sup>

### Dimensions

Stripped length 8.0 mm

PCB hole diameter 1.3 mm

### Materials

Clamp Brass

Screw Steel

Solder tab Copper Alloy

### Insulating Material

Material PA 6.6

Flammability class UL 94 V-0

### Temperatures

Operating temperature -40 °C (without mech. load) - 105 °C

Store temperature -40 °C - 105 °C

### Wave Soldering Process

Soldering temperature, recommended 260 °C

Peak soldering time, recommended 3-4 s

**Technical Data // AK700/..-5.0-H-GREEN**

Spacing 5.0 mm

**Reflow Process**

Soldering temperature, recommended -

Peak soldering time, recommended -

**Colours**

GREEN, RAL 6018



GREY, RAL 7016

PEBBLE GREY, RAL 7032

BLUE, RAL 5015

LIGHT GREEN, similar RAL 6018

Colours according to RAL, there may be variations on colour due to production conditions.  
Special colours on request.**Ratings**

					
UseGroup	B	C	D		
Rated voltage	300 V	-	300 V	250 V	
Rated current	15 A	-	10 A	24 A	
Rated wire size				min	max
- solid	AWG 30-12	-	AWG 30-12	0.5 mm <sup>2</sup>	4.0 mm <sup>2</sup>
- stranded	-	-	-	-	-
- stranded (flexible)	AWG 30-12	-	AWG 30-12	0.5 mm <sup>2</sup>	2.5 mm <sup>2</sup>
Torque	0.45 Nm	-	0.45 Nm	0.50 Nm	
Screw size	M3	-	M3	M3	
Test voltage	1.60 kV	-	1.60 kV	2.0 kV	

**Accessoires**

Figure	Designation	Article Number
	Bridge, 2-pole, insulated, BRI/2-5.0/5.08-LIGHT GREY	Art.-Nr. 50000000006
	Bridge, 3-pole, insulated, BRI/3-5.0/5.08-LIGHT GREY	Art.-Nr. 50000000007
	Bridge, 2-pole, BR/2-5.0/5.08-L7.0	Art.-Nr. 50000000008
	Screw Cover SC-AK700-YELLOW	Art.-Nr. 50700000004



Technical Data // **AK700/..-5.0-H-GREEN**

Spacing 5.0 mm

**Order Data (Spacing 5.0 mm)**

Number of Poles	Width (mm)	Article Designation	Article Number	PU
2	10.60	AK700/2-5.0-H-GREEN	50700020261 F	200
3	15.60	AK700/3-5.0-H-GREEN	50700030261 F	200
4	20.60	AK700/4-5.0-H-GREEN	50700040261 F	200
5	25.60	AK700/5-5.0-H-GREEN	50700050261 F	200
6	30.60	AK700/6-5.0-H-GREEN	50700060261 E	100
7	35.60	AK700/7-5.0-H-GREEN	50700070261 E	100
8	40.60	AK700/8-5.0-H-GREEN	50700080261 E	100
9	45.60	AK700/9-5.0-H-GREEN	50700090261 E	100
10	50.60	AK700/10-5.0-H-GREEN	50700100261 D	50
11	55.60	AK700/11-5.0-H-GREEN	50700110261 D	50
12	60.60	AK700/12-5.0-H-GREEN	50700120261 D	50

**Technical drawing**

