



Specifications:
 Current Rating: 3.0A AC,DC
 Contact Resistance: 20m ohm.Max
 Insulation Resistance: 1,000M ohm.Min
 Withstanding Voltage: 500V AC/Minute
 Operating Temperature Range: -40°C~+105°C

Material:
 Insulator: High Temperature Plastic (UL94V-0)
 Insulator Color: Ivory/Black
 Contact: Copper Alloy
 Plated: Gold/Matte Tin/Selective Gold Plated

How To Order
 2211SM-XXX-BX-XX-XX

- TB:Tube
- CR:Cap+Tap&Reel
- Blank Ivory
- BK:Black
- B1:B1 Type
- B2:B2 Type
- G:Gold Plated
- MT:Matte Tin Plated
- SG:Gold Plated On Contact Area,
Matte Tin Plated On Solder Tail.
- No. of Contacts
- SMD Type

RoHS Compliant

F				DRAWN:	GENERAL TOLERANCE:	Neltron Industrial Co., Ltd.	SIZE
E				MEI	.X=±0.30 .XX=±0.20		
D				CHECKED:	UNIT: MM	DESCRIPTION: 2.54mm Pin Header Single Row Straight SMD Type	A4
C				JERRY	SCALE: 1:1		
B	21-FEB-2024	Update Drawing	Jamie	APPROVAL:	SHEET: 1/1	PART NO: 2211SM-XXX-BX-XX-XX	
A	19-JAN-2022		MEI	RORY	PROJECTION:		
REV	DATE	FILE	BY				