



Specifications:
 Current Rating: 3.0A AC,DC
 Contact Resistance: 20m ohm.Max
 Insulation Resistance: 1,000M ohm.Min
 Withstanding Voltage: 500V AC/Minute
 Operating Temperature Range: -40°C~+105°C

Material:
 Insulator: High Temperature Plastic (UL94V-0)
 Insulator Color: Ivory/Black
 Contact: Copper Alloy
 Plated: Gold/Matte Tin/Selective Gold Plated

How To Order
 2211SM-XXX-BX-XX-XX

- TB:Tube
- CR:Cap+Tap&Reel
- Blank Ivory
- BK:Black
- B1:B1 Type
- B2:B2 Type
- G:Gold Plated
- MT:Matte Tin Plated
- SG:Gold Plated On Contact Area,
Matte Tin Plated On Solder Tail.
- No. of Contacts
- SMD Type

F			
E			
D			
C			
B	21-FEB-2024	Update Drawing	Jamie
A	19-JAN-2022		MEI
REV	DATE	FILE	BY

DRAWN: MEI
 CHECKED: JERRY
 APPROVAL: RORY

GENERAL TOLERANCE:
 .X=±0.30
 .XX=±0.20

UNIT: MM
 SCALE: 1:1
 SHEET: 1/1
 PROJECTION:

Neltron Connectors **Neltron Industrial Co., Ltd.**

DESCRIPTION:
 2.54mm Pin Header Single Row Straight SMD Type

PART NO:
 2211SM-XXX-BX-XX-XX

RoHS Compliant

SIZE
A4