



Specifications:
 Current Rating: 3.0A AC, DC
 Voltage Rating: 500V AC, DC
 Contact Resistance: 30m ohm Max
 Insulation Resistance: 5000M ohm Min
 Withstanding Voltage: 650V AC/minute
 Operating Temperature Range: -40°C ~ +105°C
 Material:
 Insulator Material: PBT (UL94V-0)
 Contact Material: Copper Alloy
 Finish: Gold Plated

2228AG=4.5mm Length Open Type (BK)
 2228BG=6.47mm Length Gth Close Type (BK,BU,RD,YL,WH,GN)
 2228CG=5.97mm Length Open Type (BK,BU,RD,YL,WH,GN)
 2228DG=8.0mm Length Open Type (BK)
 2228EG=8.5mm Length Close Type (BK)
 2228GG=13.5mm Length W/Handle (BK) Δ
 13.65mm Length W/Handle (BU,RD,YL,WH,GN)

How to order
 2228XG-XX

Insulator color
 Standard Black Color
 BU=blue
 RD=red
 YL=yellow
 WH=white
 GN=green
 Type
 A/B/C/D/E/G

ROHS Compliant

REV	DATE	FILE	BY
A	02-Jul-2004		Cel king
B	02-Jan-2006	ECN-CN051210	Wendy
C	27-Mar-2014	ECN-TW1403011	Cherry
D	06-Feb-2020	modify 2228GG Length	Romina
E			

DRAWN: Cel king
 CHECKED: ANT
 APPROVAL: Mike Wu

GENERAL TOLERANCE:
 X.X = ± 0.2
 X.XX = ± 0.15

UNIT: MM
 SCALE:
 SHEET: 1 / 1
 PROJECTION:

Neltron Industrial Co., Ltd.

DESCRIPTION: 2.54mm Mini Jumper

PART NO: 2228XG-XX

SIZE: **A4**