




未注公差/General tolerances (mm)													
0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	0.1/10 ±2'
~3	~6	~10	~18	~30	~50	~80	~120	~180	~250	~315	~400	>500	
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50
间距/Pitch(mm) / 线数范围/Poles										3.5/N=136P			
使用温度范围/Operating temperature(°C)										-40~+110			
符合 RoHS 环保要求/Conform to RoHS										Yes			



DEGSON		MATERIAL: PC	SURFACE/COLOR: /	
		MAT NO./REV: /	MAT STATUS: /	
APPD: Peng M	2022.06.09	NAME		
CHKD: Gao WG	2022.06.09	ZSF3.5-136P-1Y-00A(H)		
DRFT: Chen KZ	2022.06.09	DRAWING NO. /	TYPE	DRAWING STATUS
		CUSTOMER DRAWING		/
REV	ECN	DESCRIPTION	SCALE	SHEET
00	/	/	1:1	1/1

00	/	/	Chen KZ	2022.06.09
REV	ECN	DESCRIPTION	DRFT	DATE

Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless authorized in writing by the copyright holder. All rights reserved for patent. 除专利注明情况外，其他内容均受版权法保护。未经许可，不得复制或传播。 除专利注明情况外，其他内容均受版权法保护。 除专利注明情况外，其他内容均受版权法保护。