









未注公差/General tolerances(mm)											0.1/10		
0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250		>315	>400
~3	~6	~10	~18	~30	~50	~80	~120	~180	~250	~315	~400	~500	~2.50
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50



文管中心  
研发专用  
2020.06.02  
(仅限内部使用, 对外无效)



3	Screw cap	Copper alloy	M2.5
2	Pin	Copper alloy	Sn Plated
1	Housing	PA66	UL94V-0
ITEM	NAME OF PART	MATERIAL	NOTES

UL 标准/UL Standard:		B
额定电压/电流/Rated Voltage(V)/Current(A)		300/8
EC 标准/IEC Standard:		
过压类别/Overvoltage Category/污染等级/Pollution Degree		II/2
额定电压/电流/Rated Voltage(V)/Current(A)		250/7
额定脉冲电压(KV)/Rate Impulse Voltage(KV)		2.5
间距/Pitch(mm)/线数范围/Poles		3.50/N=02~22P
使用温度范围/Operating temperature(°C)		-40~+105
符合RoHS环保要求/Conform to RoHS		Yes

MATERIAL:		SURFACE:						
MAT NO.:	/	宁波高松电子有限公司 NINGBO DEGSON ELECTRICAL CO., LTD						
STATUS:	/							
APPD: Lan ChH	2020.06.02							
CHKD:	/	NAME: 15EDGVM-3.5-XXP-1Y-00A(H)						
DRFT: Yz	2015.10.13	DRAWING NO.:	15EDGVM-3.5-C01					
REV	ECN	DESCRIPTION	DRFT	DATE	TYPE: CUSTOMER DRAWING	SCALE: 2.5:1	SHEET	1/1

T2	Change the drawing and tolerance table	Yu JZh	2020.06.02	
REV	ECN	DESCRIPTION	DRFT	DATE