

Specifications:


Current rating:2Amps  
 Voltage rating:250V AC,DC  
 Contact resistance:20m ohm Max  
 Insulation resistance:1,000M ohm min.  
 Dielectric Withstanding:1000V AC/Minute  
 Operating Temperature:-25°C ~ +85°C

Materials:

Insulator:Nylon 66 UL94V-0  
 Insulator Color:White

How To Order

2318HEH-XX



Dimension Information:

Circuits	Dim.A	Dim.B	Circuits	Dim.A	Dim.B
2	2.50	7.00	10	22.50	27.00
3	5.00	9.50	11	25.00	29.50
4	7.50	12.00	12	27.50	32.00
5	10.00	14.50	13	30.00	34.50
6	12.50	17.00	14	32.50	37.00
7	15.00	19.50	15	35.00	39.50
8	17.50	22.00	15	35.00	39.50
9	20.00	24.50	16	37.50	42.00

RoHS Compliant

F				DRAWN:	GENERAL TOLERANCE:	<b>Neltron Industrial Co., Ltd.</b>	DESCRIPTION:	SIZE
E				Andrew	.X=±0.50 .XX=±0.25			
D				CHECKED:	UNIT: MM	2.5mm Wire To Board Housing	PART NO:	A4
C				Bill He	SCALE: 1:1			
B				APPROVAL:	SHEET: 1 / 1	2318HEH-XX		
A	18-Jun-2020		Andrew	Bill He	PROJECTION:			
REV	DATE	FILE	BY					