

Specifications:


Current Rating:3.0A AC/DC
 Contact Resistance:20m Ohm Max
 Insulation Resistance:1000M Ohm Min.
 Withstanding Voltage:500V AC/Minute
 Operating Temperature Range:-40°C To +105°C

Material and Finish:

Insulator:Nylon 66 (UL94V-2)
 Insulator Color:White
 Contact:Brass
 Plating:Tin Plated

How To Order

2217S-XX-WH2



P.C.B layout

RoHS Compliant

| | | | | | | | | |
|-----|-------------|------|------------|----------------------|--------------------|-------------------------------------|--|-------------------|
| F | | | | DRAWN: | GENERAL TOLERANCE: | Neltron Industrial Co., Ltd. | DESCRIPTION: 2.54mm Wire to Board Wafer Straight Type | SIZE A4 |
| E | | | Romina Wu | .X=±0.2 .XX=±0.15 | | | | |
| D | | | CHECKED: | UNIT: MM | | | | |
| C | | | Jerry Chen | SCALE:1:1 | | | | |
| B | | | APPROVAL: | SHEET: 1 / 1 | PART NO: | 2217S-XX-WH2 | | |
| A | 08-May-2019 | | Romina Wu | PROJECTION: | | | | |
| REV | DATE | FILE | BY | Rory Chen | | | | |